











# National Emission Standards for Hazardous Air Pollutants for Reciprocating Internal Combustion Engines (RICE Rule)



# 40 CFR 63 Subpart ZZZZ Area Source New Emergency Engine >500 Horsepower



## **Compliance Requirements**

You must comply with either the Compression Ignition (CI) or Spark Ignition (SI) New Source Performance Standards (NSPS), as applicable, upon startup.







# You are subject to the CI NSPS (40 CFR 60 Subpart IIII) if your emergency CI engine was:

-Constructed (ordered\*) after July 11, 2005 AND manufactured after April 1, 2006 (July 1, 2006 for fire pump engines)

OR

-Modified/reconstructed after July 11, 2005

\*NOTE: For the purposes of this rule, the date that construction commences is the date the engine is ordered by the owner or operator.



#### If you are subject to the CI NSPS, you must meet these requirements:

**Emission and Operating Limits, Testing Requirements, Monitoring Requirements:** 

- See Table
- •Must meet these standards for the life of the engine

#### **Fuel Requirements:**

- •As of October 1, 2007 500 ppm sulfur diesel (LSD)
- •As of October 1, 2010 15 ppm sulfur diesel (ULSD) for engines <30 l/cyl displacement
  - -You may use up any diesel fuel acquired prior to October 1, 2010 that does not meet the requirements for nonroad diesel fuel.
- •As of June 1, 2012 1,000 ppm sulfur diesel for engines ≥30 l/cyl displacement



#### If you are subject to the CI NSPS, you must meet these requirements:

#### **Compliance Requirements:**

- •If you have 2007 model year or later engine with displacement <30 l/cyl or a fire pump engine, 2008-2011 model year or later, depending on engine size
  - Purchase certified engine
  - •Install, configure, operate and maintain engine per manufacturer's instructions/procedures
    - Performance testing not required
    - -Can operate differently than manufacturer's recommendations, but must then do performance test to show compliance
- •Engines not required to be certified (Choose one of the following to demonstrate compliance):
  - Purchase certified engine
  - •Keep records of performance test conducted on similar engine
  - •Keep records of engine manufacturer data indicating compliance
  - •Keep records of control device vendor data indicating compliance
  - Conduct initial performance test
- •Engines ≥30 l/cyl displacement:
  - Initial performance test
  - Continuously monitor operating parameters





#### Recordkeeping/Reporting:

- •Install non-resettable hour meter and record hours of operation
- •If engine is equipped with diesel particulate filter (DPF):
  - -Install backpressure monitor and keep records of corrective actions





Emergency CI Engine Category	Date Constructed/ Reconstructed/ Manufactured	Emission Standards <sup>a,b,c,d</sup>	Importing/ Installing Requirements	Compliance Requirements	Testing Requirements	General Provisions (40 CFR part 60)
Pre-2007 model year <10 l/cyl (except fire pump engines)	Commenced construction	60.4205(a) Table 1			60.4212	Table 8
Pre-2007 model year 10 l/cyl≤displacement<30 l/cyl (except fire pump engines)	after 7/11/2005 and manufactured after 4/1/2006	60.4205(a) 40 CFR 94.8(a)(1)	60.4208(a), (b), (h), (i)	60.4211(a), (b), (f), (g)		
2007 model year and later <30 l/cyl (except fire pump engines)		60.4205(b) 60.4202		60.4211(a), (c), (f), (g)		
Fire pump engines <30 l/cyl manufactured prior to the model years in Table 3 of 40 CFR part 60, subpart IIII	Commenced construction after 7/11/2005 and	60.4205(c) Table 4	60.4208(h), (i)	60.4211(a), (b), (f), (g)		
Fire pump engines <30 l/cyl manufactured during or after the model year that applies to your fire pump engine power rating in Table 3 of 40 CFR part 60, subpart IIII				60.4211(a), (c), (f), (g)		
≥30 l/cyl (except fire pump engines)	Commenced construction after 7/11/2005 and manufactured after 4/1/2006	60.4205(d)(1) and (2)	60.4208(a), (b), (h), (i)	60.4211(a), (d), (f), (g)	60.4213	
Modified/Reconstructed <30 l/cyl	Modified or reconstructed after 7/11/2005	Pre-2007 Model Year: 60.4205(a) 2007 Model Year and Later: 60.4205(b)	60.4208(i)	60.4211(a), (e), (f), (g)	60.4212 60.4204(e)	
Modified/Reconstructed		60.4205(d)(1)-(3)			60.4213	

<sup>&</sup>lt;sup>a</sup>Per 60.4200(e), facilities with CI ICE that are acting as temporary replacement units and that are located at a stationary source for <1 year and that have been properly certified as meeting the standards that would be applicable to such engine under the appropriate nonroad engine provisions, are not required to meet any other provisions under this rule with regard to such engines' requirements in 40 CFR 60.4207.

 $<sup>^{</sup>c}$ ICE with a displacement of  $\geq$ 30 l/cyl that are used in Guam, American Samoa, or the Commonwealth of the Northern Mariana Islands are required to meet the emission standards in 60.4215(c).  $^{d}$ Special requirements apply to engines used in Alaska. Please refer to 60.4216 for the specific requirements that apply.



≥30 1/cyl

<sup>&</sup>lt;sup>b</sup>Per 60.4215(a), ICE with a displacement of <30 l/cyl that are used in Guam, American Samoa, or the Commonwealth of the Northern Mariana Islands are required to meet the applicable emission standards in §60.4202 and §60.4205.

### Spark Ignition New Source Performance Standards (SI NSPS)

# You are subject to the SI NSPS (40 CFR 60 Subpart JJJJ) if your emergency SI engine was:

-Constructed (ordered) after June 12, 2006 AND manufactured on/after January 1, 2009 OR

-Modified/reconstructed after June 12, 2006

\*NOTE: For the purposes of this rule, the date that construction commences is the date the engine is ordered by the owner or operator.



### Spark Ignition New Source Performance Standards (SI NSPS)

#### If you are subject to the SI NSPS, you must meet these requirements:

- •Emission and Operating Limits, Testing Requirements, Monitoring Requirements:
  - See Table
  - •Must meet these standards for the life of the engine

#### •Fuel Requirements:

•If using gasoline, gasoline must meet sulfur limit: cap of 80 ppm/gal

#### Compliance Requirements:

- •If you have a *certified* engine:
  - •Install, operate, and maintain engine according to manufacturer's instructions
  - •If you do not operate/maintain according to manufacturer's instructions:
    - -Keep maintenance plan and maintenance records, operate consistent with good air pollution control practices
    - -Initial performance test and subsequent testing every 8,760 hours or 3 years, whichever is first
- •If you have a *non-certified* engine:
  - Maintenance plan
  - •Initial test and subsequent testing every 8,760 hours or 3 years, whichever is first



### Spark Ignition New Source Performance Standards (SI NSPS)

# If you are subject to the SI NSPS, you must meet these requirements:

#### •Monitoring Requirements:

•Install non-resettable hour meter if engine was built on/after July 1, 2010

#### •Recordkeeping/Reporting:

- Documentation of certification (EPA Certificate of Conformity)
- •Records of engine maintenance
- •Records of hours of operation
- Initial notification for non-certified engines
- •Notification of Intent to Conduct Performance Testing 30 days prior to test
- •Results of performance testing within 60 days of test



Photo credit: EPA





#### UNITED STATES ENVIRONMENTAL PROTECTION AGENCY 2012 MODEL YEAR CERTIFICATE OF CONFORMITY WITH THE CLEAN AIR ACT OF 1990

OFFICE OF TRANSPORTATION AND AIR QUALITY ANN ARBOR, MICHIGAN 48105

Certificate Issued To: Generac Power Systems, Inc.

(U.S. Manufacturer or importer)

Certificate Number: CGNXB06.82NN-012

Effective Date: 10/26/2011

Expiration Date: 12/31/2012 Byron J. Burker, Acting Division Director

Issue Date: 10/26/2011

Revision Date:

Manufacturer: Generac Power Systems, Inc.

Engine Family: CGNXB06.82NN

Certificate Number: CGNXB06.82NN-012 Certification Type: Stationary (Part 60)

Fuel: Natural Gas (CNG/LNG)

Emission Standards: NMHC + NOx (g/kW-hr): 13.4

CO (g/kW-hr): 519 HC + NOx (g/kW-hr): 13.4 Emergency Use Only: Y

Pursuant to Section 213 of the Clean Air Act (42 U.S.C. section 7547) and 40 CFR Part 60, 1065, 1068, and 60 ( stationary only and combined stationary and mobile ) and subject to the terms and conditions prescribed in those provisions, this certificate of conformity is hereby issued with respect to the test engines which have been found to conform to applicable requirements and which represent the following nonround engines, by engine family, more fully described in the documentation required by 40 CFR Part 50 and produced in the stated model year.

This certificate of conformity covers only those new nonroad spark-ignition engines which conform in all material respects to the design specifications that applied to those engines described in the documentation required by 40 CFR Part 60 and which are produced during the model year stated on this certificate of the said manufacturer, as defined in 40 CFR Part 60. This certificate of conformity does not cover nonroad engines imported prior to the effective date of the certificate.

It is a term of this certificate that the manufacturer shall consent to all inspections described in 40 CFR 1068.20 and authorized in a warrant or court order. Failure to comply with the requirements of such a warrant or court order may lead to revocation or suspension of this certificate for reasons specified in 40 CFR Part 60. It is also a term of this certificate that this certificate may be revoked or suspended or rendered yould ab initio for other reasons specified in 40 CFR Part 60.

This certificate does not cover large nonroad engines sold, offered for sale, or introduced, or delivered for introduction, into commerce in the U.S. prior to the effective date of the certificate.

50

	Date			Importing/	Compliance Requirements			Notification,	General	
Emergency SI Constructed Engine Reconstructed		Size/Engine	Emission	Importing/ Installing	Engines being operated and maintained in a certified manner <sup>2</sup>		Engines being operated and maintained in a non-certified manner <sup>3</sup>		Reports, and	Provisions
Category	/ Manufactured	Type/Fuel	e/Fuel Standards Requiren	Requirements 5	General Compliance	<b>Performance Testing</b>	Conoral		Records Requirements	(40 CFR part 60)
		Gasoline	60.4231(b) 60.4233(b)	60.4236(c),(d)	60.4243(a)(1) If using AFRC: 60.4243(g) 40 CFR part	Ć:		60.4243(a)(2)(iii) <sup>4</sup>	60.4245(a),	
Commenced construction after 6/12/2006 and manufactured on or after 1/1/2009	Rich Burn LPG	60.4231(c) 60.4233(c)	60.4236(c),(d)	1068, subparts A-D. 60.4243(d)	None	60.4243(d) If using AFRC: 60.4243(g) 60.4243(a)(2)(iii )  60.4243(e)  Fortified:  60.4244  All: If natural gas engine and using propane as alternative fuel for >100 hrs/yr: 60.4243(e)  Certified:		(b), (e)		
	≥100 HP (except gasoline and rich burn LPG)	60.4233(e) <sup>4</sup> Table 1	60.4236(c)	60.4243(d) If using AFRC: 60.4243(g) Certified: 60.4243(b)(1) Non-certified: 60.4243(b)(2)	All: If natural gas engine and using propane as alternative fuel for more than 100 hrs/yr: 60.4243(e) Non-Certified: 60.4243(b)(2)(ii), 60.4244		60.4245(a), (b), (e) If natural gas engine and using propane as alternative fuel solely during emergency operations: 60.4243(e)	60.4246 Table 3		
Reconstructe reconstructed	Modified or	Gasoline	60.4233(f)(2)	None						
		Rich Burn LPG	60.4233(f)(3)		If using AFRC: 60.4243(g) 60.4243(i)			60.4245(a),(d), (e) 60.4245(b)		
	reconstructed after 6/12/2006	Natural gas and lean burn LPG	60.4233(f)(4)							
		Landfill/Digester Gas	60.4233(f)(5)							

Facilities with engines acting as temporary replacement units and that are located at a stationary source for <1 year and that have been properly certified as meeting the standards that would be applicable to such engine under the appropriate nonroad engine provisions, are not required to meet any other provisions under this rule with regard to such engines.

<sup>&</sup>lt;sup>5</sup>The requirements of this section do not apply to ICE that have been modified or reconstructed, and they do not apply to engines that were removed from one existing location and reinstalled at a new location.



If you operate and maintain the certified engine and control device according to the manufacturer's emission-related instructions, you are operating in a certified manner.

<sup>&</sup>lt;sup>3</sup>If you do not operate and maintain the certified engine and control device according to manufacturer's emission-related instructions, you engine will be considered a non-certified engine.

<sup>4</sup>If you own/operate an engine ≤500 HP and you purchase a non-certified engine or you do not operate and maintain your certified engine and control device according to the manufacturer's emission-related instructions, you must perform initial performance testing as indicated in this section, but you are not required to conduct subsequent testing unless the engine is rebuilt or undergoes major repair or maintenance. A rebuilt ICE means an engine that has been rebuilt as that term is defined in 40 CFR 94.11(a).

#### **NSPS Emergency Engine Requirements**

- •No limit on hours of operation for emergency service (i.e. hurricane or ice storm)
  - -Do not operate the engine for more than 30 minutes before the emergency condition is expected to occur; terminate engine operation immediately upon notification that the emergency condition is no longer imminent.
- •100 hours/year allowed for maintenance and testing
- •50 hours/year allowed for non-emergencies (counts as part of the 100 hour/year maintenance and testing limit)
  - -Cannot be used for peak shaving or non-emergency demand response, or to generate income for a facility to an electric grid or otherwise supply power as part of a financial arrangement unless <u>all</u> of the following conditions are met:
    - Engine is dispatched by the local balancing authority or local transmission and distribution system operator
    - Dispatch is intended to mitigate local transmissions and/or distribution limitations so as to avert potential voltage collapse or line overloads that could lead to the interruption of power supply in a local area or region
    - Dispatch follows reliability, emergency operation or similar protocols that follow specified North American Electric Reliability Corporation (NERC), regional, state, public utility commission or local standards or guidelines
    - Power is provided only to the facility itself or to support the local transmission and distribution system
    - Owner/operator identifies and records the entity that dispatches the engine and the specific NERC, regional, state, public utility commission or local standards or guidelines that are being followed for dispatching the engine. The local balancing authority or local transmission and distribution system operator may keep these records on behalf of the engine owner/operator.

Note: If operation in response to a deviation of voltage from the electricity supplier to the premises does not qualify as emergency operation under the rule, the unit may operate for up to 50 hours/year as part of the non-emergency operation allowance as long as the engine is not used for peak shaving or as part of a financial arrangement with another entity. Contact EPA if you have any questions. The following are examples of when a voltage deviation might be considered an emergency:

- Voltage deviation at a hospital which disrupts normal operations
- Deviation in power to a 911 call center
- Power disruption at a shopping mall which affects lighting and prevents shoppers from exiting the building safely



# **Emergency Engine Requirements**

- If emergency engine operates for more than allowable hours for non-emergency purposes, it will need to meet all non-emergency engine requirements.
- If engine is located in CT, also comply with CT emergency engine requirements.
- If located elsewhere, comply with State emergency engine requirements.





Photo credit: EPA

# **Emergency Engine Requirements**

#### •If you operate for local reliability:

- -Collect and submit an annual report including location, dates and times of operation.
  - •First report must cover calendar year 2015 and is due March 31, 2016.
  - •Submit electronically using the form in the Compliance and Emissions Data Reporting Interface that is accessed through EPA's Central Data Exchange at www.epa.gov/cdx.





# CT Emergency Engine Definition

According to Sec. 22a-174-22(a)(3) of the RCSA, "emergency engine" means a stationary reciprocating engine or a turbine engine which:

- Provides mechanical/electrical power only during periods of
  - -testing and scheduled maintenance or
  - -during an emergency or
  - -in accordance with a contract ensuring electricity for use within the state of CT during an OP-4, Step 6 event
- Does <u>not</u> include an engine for which the owner/operator is party to any other
  agreement to sell electrical power from such engine to an electricity supplier, or
  otherwise receives any reduction in the cost of electrical power for agreeing to
  produce power during periods of reduced voltage or reduced power availability.

**Note:** Engines operating under RCSA Sections 22a-174-3b and 3c must comply with additional requirements



# CT Emergency Engine Requirements

- •Only operate during emergencies, maintenance/scheduled testing, or during an OP-4, Step 6 event
- •Emergency hrs of operation: no limit (unless subject to 22a-174-3b or 3c)
- •Engine cannot be used as part of any other agreement or financial arrangement with another entity

#### If operating under RCSA Sec. 22a-174-3b:

- Emergency hrs of operation: 300 hr/yr limit
- •Any nongaseous fuel consumed by engine shall not exceed sulfur content of 0.0015%, dry basis

#### If operating under RCSA Sec. 22a-174-3c:

No restriction on hrs of use or fuel sulfur content; however, total facility purchases of fuel are extremely limited



### CT and Federal Emergency Engine Requirements

Federal Only	Common to Both	State Only
<ul> <li>100 hr/yr limit:         <ul> <li>Testing and maintenance checks</li> <li>Readiness testing</li> </ul> </li> <li>50 hr/yr of the 100 hr/yr limit:         <ul> <li>Non-emergencies if no financial arrangement</li> <li>50 hr/yr allowed for peak shaving, non-emergency demand response, or to generate income for a facility</li> </ul> </li> </ul>	•Emergency hrs of operation: no limit (unless subject to 22a-174-3b or 3c)	<ul> <li>Only operate during emergencies, maintenance/scheduled testing, or during an OP-4, Step 6 event</li> <li>Engine cannot be used as part of any other agreement or financial arrangement with another entity</li> <li>If operating under RCSA Sec. 22a-174-3b:</li> <li>Emergency hrs of operation:</li> </ul>
to an electric grid or otherwise supply power as part of a financial arrangement if <u>all</u> specified conditions are met		300 hr/yr limit  •Any nongaseous fuel consumed by engine shall not exceed sulfur content of 0.0015%, dry basis
		If operating under RCSA Sec. 22a-174-3c: No restriction on hrs of use or fuel sulfur content, however total facility purchases of fuel are extremely limited



### Where do I send notifications and reports?

Unless otherwise specified, send reports to:



US Environmental Protection Agency
5 Post Office Square, Suite 100, Mail code: OES04-2

Boston, MA 02109-3912


Attention: Air Clerk



# Visit the EPA RICE Compliance Page

### www.epa.gov/ttn/atw/icengines

- Fact sheets
- Regulations
- Example notifications
- Announcements
- Q & A documents
- Testing advice
- Recorded webinars
- ...and more!





# Take Aways

#### **Engine Type:**

•A new or reconstructed emergency engine at an area source with a site rating of greater than 500 horsepower

#### **Compliance Date:**

Upon startup

#### **Compliance Requirements:**

- •Comply with all CI or SI NSPS requirements, if applicable
- •Comply with all NSPS and State emergency engine requirements

