

Connecticut Department of

**ENERGY &
ENVIRONMENTAL
PROTECTION**

**BUREAU OF AIR MANAGEMENT
NEW SOURCE REVIEW PERMIT
TO CONSTRUCT AND OPERATE A STATIONARY SOURCE**

Issued pursuant to Title 22a of the Connecticut General Statutes (CGS) and Section 22a-174-3a of the Regulations of Connecticut State Agencies (RCSA).

Owner/Operator	Firestone Building Products Company, LLC
Address	780 James P. Casey Drive, Bristol, CT 06010
Equipment Location	780 James P. Casey Drive, Bristol, CT 06010
Equipment Description	Foam Insulation Board Manufacturing Line
Town-Permit Numbers	026-0045
Premises Number	0019
Stack Number	16
Modification Issue Date	February 2, 2018
Prior Permit Issue Dates	November 25, 1997 (Permit to Construct & Operate) December 6, 2000 (Revision) April 26, 2002 (Minor Modification) March 7, 2005 (Minor Modification) November 30, 2009 (Minor Modification) May 21, 2014 (Minor Modification) February 22, 2017 (Non-Minor Modification)
Expiration Date	None

/s/ Anne Gobin for
Robert J. Klee
Commissioner

February 2, 2018
Date

This permit specifies necessary terms and conditions for the operation of this equipment to comply with state and federal air quality standards. The Permittee shall at all times comply with the terms and conditions stated herein.

PART I. DESIGN SPECIFICATIONS

A. General Description


Firestone Building Products Company operates a foam insulation board manufacturing line. The foam insulation board manufacturing line consists of storage tanks for blowing agents and reactant chemicals, various process vessels, a heated conveyor (laminator), conveyors and trim and crosscut saws. VOC emissions from the laminator are controlled by the regenerative thermal oxidizer (RTO). Particulate emissions from sawing are controlled by a dust collector. The sawing also releases VOC from the foam, which go through the dust collector. The dust collector gases are ducted directly to a zeolite rotary concentrator to remove VOCs. An additional filter media (fabric filter and HEPA filter) polishes the remaining particulate before the concentrator. The concentrated VOCs are ducted to the RTO. The Concentrator clean side exhausts indoors to the building truck loading bay.

Side A (Methylene Di-p-phenylene Isocyanate (MDI)) and Side B (blowing agent formulation, polyester polyol, flame retardant, surfactant and amine catalysts) (see Figure 1) chemicals are combined just before the exit from the laydown nozzle. Multiple streams of the mixture are deposited on the bottom paper backing located on a conveyor. The bottom paper backing is conveyed into the laminator along with the top paper backing. The paper backing is also referred to as “*facer*”. The foam expands to fill the space between the paper backings to form a continuous length panel. The thickness of the foam insulation board varies depending on the line speed and laminator settings. Sidewalls along the conveyors force the expanding foam to conform to the width of the paper backing. The continuous sheet is cured in the heated section of the laminator, and then the sides are cut by the edge trim saws and crosscut into 16-foot sections and transferred to a gang saw where they are cut into either 4 or 8 foot segments. The cut boards travel on a conveyor to a station where they are stacked and shrink wrapped. The wrapped boards are then stacked and stored in the finished goods warehouse area pending shipment.

At times, the facility will experiment with alternative chemicals that make up Side A and B formulations for product development and improvement. Trial chemicals will be tracked in accordance with corresponding permit conditions.

The chemicals that make up Side A and Side B formulations are contained in process and storage tanks, all of which are subject to change due to the ongoing product development and improvement.

Figure 1



B. Equipment Design Specifications

1. Maximum Hourly Material Usage:

<u>Foam Board Chemicals</u>	<u>Maximum Usage (lb/hr)</u>
a. Side A	9,045
b. Side B	6,625
c. Total Side A & B:	15,670

C. Control Equipment Design Specifications

1. Baghouse Filter:
 - a. Pollutant Controlled: PM
 - b. Make & Model No: Flex-Kleen 84 WSTS 169 III
 - c. Bag Material: Polyester
 - d. Air/Cloth Ratio: 7.48:1
 - e. Cleaning Method: Pulses of compressed air
 - f. Expected PM₁₀ Collection Efficiency: 99.5%
 - g. Baghouse is vented to Concentrator wheel, which is protected by a filter system including a HEPA filter with 99.99% removal efficiency by design. (Clean side of baghouse/concentrator exhausts indoors to truck loading bay.)

2. Regenerative Thermal Oxidizer (RTO)/Rotary Concentrator:
 - a. Pollutant Controlled: VOC
 - b. Make & Model No.: Crawford Equipment Co. 10.0-RTO-95
 - c. Fuel Type: Natural Gas
 - d. Maximum Firing Rate: 2000 ft³/hr (2 MMBtu/hr)

D. Stack Parameters

1. Minimum Stack Height (ft): 45
2. Design Exhaust Gas Flow Rate (acfm): 10,000
3. Minimum Stack Exit Temperature (°F): 100
4. Minimum Distance from Stack to Property Line (ft): 500

PART II. OPERATIONAL CONDITIONS

A. Equipment

1. Blowing agent formulation shall not exceed 1,254 pounds per hour and 8% of total foam board chemicals used. Pentane, acetone or other chemicals may be used in the blowing agent formulation. The emissions from any new compounds, for production or trial runs, shall be counted toward any applicable emissions limit in this permit.
2. Maximum Annual Foam Board Chemicals Used, does not include facer weight: 25,900 tons/consecutive 12 months.
3. Lachenmeir Shrink Wrap:
 - a. Fuel Type: Natural Gas

B. Control Equipment

1. RTO/Rotary Concentrator:
 - a. Rotary Concentrator Desorption Flow Temperature Range (°F): 300-410
 - b. Minimum RTO Combustion Temperature (°F): 1,400
 - c. Minimum RTO Combustion Chamber Retention Time: 1 second
 - d. Minimum RTO Destruction Efficiency: 95%
 - e. Minimum RTO/Concentrator Combined Destruction Efficiency: 90%

- C. The Permittee shall operate and maintain this equipment in accordance with the manufacturer's specifications and written recommendations.
- D. The Permittee shall properly operate the control equipment at all times that this equipment is in operation and emitting air pollutants.
- E. The Permittee shall perform maintenance and inspections on the Lachenmeir shrink wrapper as recommended by the manufacturer.
- F. The Permittee shall perform maintenance and inspections on the RTO and rotary concentrator as recommended by their respective manufacturers. On a quarterly basis, the Permittee shall inspect the total enclosure for the laminator, the duct work for the RTO and rotary concentrator for leaks.

PART III. ALLOWABLE EMISSION LIMITS

The Permittee shall not cause or allow this equipment to exceed the emission limits stated herein at any time.

A. Criteria Pollutants

1. Manufacturing Losses (through RTO/Rotary Concentrator)

Pollutant	lb/hr	tpy
VOC	6.0	9.5

2. Fugitive Losses from Warehouse

Pollutant	tpy
VOC	59.1

3. Natural Gas Combustion Emissions from the RTO

Pollutant	tpy
PM	0.07
PM ₁₀	0.07
PM _{2.5}	0.07
SO ₂	0.005
NO _x	0.88
VOC	0.05
CO	0.74

4. Total VOC Emissions

Pollutant	tpy
VOC	68.6*

*Note: Notwithstanding Part II.A.2, total VOC emissions shall not exceed 68.9 tpy.

B. Hazardous Air Pollutants

This equipment shall not cause an exceedance of the Maximum Allowable Stack Concentration (MASC) for any hazardous air pollutant (HAP) emitted and listed in RCMA Section 22a-174-29. [STATE ONLY REQUIREMENT]

- C. Demonstration of compliance with the above emission limits may be met by calculating the emission rates using mass balance calculations and emission factors from the following sources:

1. Manufacturing VOC losses:
 - a. MDI:

$$\text{Manufacturing VOC Loss (tons/month)} = W \times [1 - \text{RTO/Concentrator Combined Destruction Efficiency}] / [453.6 \text{ g/lb}] / [2000 \text{ lb/ton}]$$

Where,
RTO/Concentrator Combined Destruction Efficiency is as determined by most recent stack test data at the FBPC Bristol, CT facility and calculated in Part III, C.1.b of this permit.

W = Evaporation loss from the process as calculated according to “MDI/Polymeric MDI Emissions Reporting Guidelines for the Polyurethane Industry”, Alliance for the Polyurethane Industries, 2004.

- b. Total Manufacturing and Sawcutting VOC Loss (including emissions from the manufacturing process, baghouse and concentrator):

Total Manufacturing VOC Loss (lb/hr) = [Total VOC emissions to the control equipment] x [1 – RTO/Concentrator Combined Destruction Efficiency]

Where,
VOC emission rates are as determined by the most recent stack test data at the FPBC Bristol, CT facility. The VOC emission rate shall be adjusted by the actual VOC fraction of the blowing agent (i.e. lb VOC/lb blowing agent)

RTO/Concentrator Combined Destruction Efficiency (DE) as determined by most recent stack test data at the FBPC Bristol, CT facility.

$$DE = \frac{(A+B) - (C+D)}{(A+B)} \times 100\%$$

A = emissions rate measured between the laminator and RTO
B = emissions rate measured between saw cutting and concentrator
C = emissions rate measured at outlet of RTO
D = emissions rate measured at outlet of concentrator

and

2. Fugitive VOC losses:

- a. Warehouse VOC Loss:

VOC Emitted from the Warehouse = [Monthly Average Blowing Agent Release factor (lbs blowing agent/100 lb foam board chemicals used)] x [VOC content of blowing agent (lb VOC/lb blowing agent)] x [total chemicals used (lbs)]/100

Where, the blowing agent release factor equals:

- i. 0.2075 lb blowing agent/100 lb foam board chemicals used if the Monthly Weighted Average Board Thickness is less than 2”, or
- ii. The result of linear interpolation based on the Monthly Weighted Average Board Thickness, and;

Board Thickness	Blowing Agent Release Emission Factor
2"	0.2075 lb/100 lbs of foam board chemicals used in the production of 2" board produced
3"	0.2956 lb/100 lbs of foam board chemicals used in the production of 3" board produced

- b. Fugitive VOC emissions from leaks in transfer lines and process piping: "Fugitive VOC Emissions in the Synthetic Organic Chemical Manufacturing Industry (SOCMI)" (EPA-625/10-8A-004), 12/84.
3. Combustion Emissions from the RTO: Compilation of Air Pollutant Emission Factors (AP-42), 5th edition, Section 1.4, Tables 1.4-1 & 2 Small Boilers less than 100 MMBTU/HR, 7/98.

Sample calculations for each of the above parameters shall be kept on-site and shall be provided to the commissioner upon request.

The commissioner may require other means (e.g. stack testing) to demonstrate compliance with the above emission limits, as allowed by state or federal statute, law or regulation.

PART IV. MONITORING, RECORD KEEPING AND REPORTING REQUIREMENTS

A. Monitoring

- 1. The Permittee shall operate a continuous monitoring and record keeping system which continuously measures and continuously records the RTO's combustion temperature. The Permittee shall calibrate or replace the thermocouple annually. If the thermocouple does not agree to within one percent (1%) of the reference, the thermocouple shall be replaced.
- 2. The Permittee shall monitor the hourly material usage for Side A, Side B and blowing agent formulation.
- 3. The Permittee shall monitor the monthly chemicals used in foam board production. Such records shall include the following:
 - a. Total weight of each board thickness produced, and
 - b. The total weight of chemicals used in foam board production during the month.
- 4. The Permittee shall monitor the natural gas usage of the RTO using either fuel purchase receipts or a non-resettable totalizing fuel meter.
- 5. The Permittee shall continuously monitor the desorption temperature of the rotary concentrator using a computer display.
- 6. The Permittee shall continuously monitor the pressure drop across the baghouse filter using a manual gauge.
- 7. The Permittee shall continuously monitor the flow rate from the laminator to the RTO.
- 8. The Permittee shall perform inspections of the dust collector as recommended by the manufacturer.

B. Record Keeping

1. The Permittee shall keep a record of the hourly, monthly and consecutive 12 month usage and composition of blowing agent formulation, Side A formulation, Side B formulations, and total chemicals used in foam board production, in pounds. The consecutive 12 month material usage shall be determined by adding the current month's usage to that of the previous 11 months. The Permittee shall make these calculations within 30 days of the previous month.
2. The Permittee shall keep a record of the board thickness in inches and the total weight in tons for all chemicals used in foam board production during each calendar month. Such records shall show the dates and times for each period of operation of the laminator.
3. The Permittee shall calculate and record the monthly weighted average board thickness of all foam board produced during the month in inches and the Monthly Blowing Agent release factor in lb/100 lbs of chemicals used. The Permittee shall make these calculations within 30 days of the previous month.
4. The Permittee shall keep records of the percentage of blowing agent formulation to total foam board chemicals used for each production run of foam board.
5. The Permittee shall calculate and record of the monthly and consecutive 12-month emissions of VOC and non-VOC regulated air pollutants in tons from each of the following operations: the laminator (sides A and B) and the warehouse. The consecutive 12-month emissions shall be determined by adding the current month's emissions to that of the previous 11 months. Calculations shall be made in accordance with the Part III.C of this permit. The Permittee shall make these records within 30 days of the previous month.
6. The Permittee shall calculate and record the monthly and consecutive 12 month PM, PM₁₀, PM_{2.5}, SO₂, NO_x, VOC, and CO emissions in units of tons for the RTO. The consecutive 12 month emissions shall be determined by adding (for each pollutant) the current month's emissions to that of the previous 11 months. Such records shall include a sample calculation for each pollutant. The Permittee shall make these calculations within 30 days of the end of the previous month.
7. The Permittee shall keep material safety data sheets (MSDS) or technical data sheets (TDS) or Safety Data Sheets (SDS) for each chemical used. Such information shall include the quantity and type of each hazardous air pollutant contained in the chemicals used. For paperwork reduction, these sheets may be kept on computer file in electronic form, access to above paperwork requirement may also be allowed via internet on-demand.
8. The Permittee shall keep records of the Maximum Allowable Stack Concentration (MASC) for any hazardous air pollutant (HAP) emitted from this source including emissions from trial runs using stack parameters from the latest stack test data.
9. The Permittee shall keep records of the annual natural gas usage for the RTO.
10. The Permittee shall continuously record the RTO combustion temperature.
11. The Permittee shall continuously record the desorption temperature of the rotary concentrator.

12. The Permittee shall continuously record the flow rate from the laminator to the RTO.
13. The Permittee shall record the pressure drop across the baghouse at least once per shift.
14. The Permittee shall record all maintenance conducted on the baghouse filter and a description of the condition of the filters upon replacement.
15. The Permittee shall record all maintenance and inspections conducted on the Lachenmeir, laminator total enclosure, and duct work to the rotary concentrator/RTO control system. Such records shall contain the date of any maintenance or inspection and any action taken by the Permittee.
16. The Permittee shall keep detailed operation and maintenance records for the RTO, including the time of operation, the date removed from service, the cause for removal from service, the date and description of each service performed, and the date put back into service.
17. The Permittee shall keep detailed records of each RTO thermocouple calibration or replacement, including the date each RTO thermocouple calibration or replacement was performed and the name of the person conducting that task.
18. The Permittee shall keep calibration and maintenance records and electronic recordings for all continuous monitoring instruments and equipment.
19. The Permittee shall keep records of the manufacturer's operation and maintenance requirements for each piece of equipment associated with this process.
20. The Permittee shall keep records of all performance tests required by the commissioner.
21. The Permittee shall keep records of the required quarterly leak inspection. These records shall include any identified leaks and any corrective actions taken.
22. The Permittee shall keep all records required by this permit for a period of no less than five years and shall submit such records to the commissioner upon request.

PART V. STACK EMISSION TEST REQUIREMENTS

Stack emission testing shall be performed in accordance with the [Emission Test Guidelines](#) available on the DEEP website.

Recurring Stack testing is required for the following within three years of the previous test:


- VOC/HC Other: RTO/Concentrator Combined Destruction Efficiency (DE)

$$1. DE = \frac{(A+B) - (C+D)}{(A+B)} \times 100\%$$

$$2. RTO Destruction Efficiency = 1 - [C/(A+B-D)] \times 100\%$$

Where,

- A = emissions rate measured between the laminator and RTO
- B = emissions rate measured between saw cutting and concentrator
- C = emissions rate measured at outlet of RTO
- D = emissions rate measured at outlet of concentrator



3. The Permittee shall submit test results within 60 days after completion of testing.

PART VI. SPECIAL REQUIREMENTS

- A. STATE ONLY REQUIREMENT: The Permittee shall not cause or permit the emission of any substance or combination of substances which creates or contributes to an odor beyond the property boundary of the premises that constitutes a nuisance as set forth in RCSA Section 22a-174-23.
- B. STATE ONLY REQUIREMENT: The Permittee shall operate this facility at all times in a manner so as not to violate or contribute significantly to the violation of any applicable state noise control regulations as set forth in RCSA Sections 22a-69-1 through 22a-69-7.4, inclusive.
- C. The Permittee shall keep all drums and vessels that contain solvents, cleaners, coatings, or cleaning rags covered when not in use, so as to minimize the amounts of VOCs emitted to the atmosphere.

PART VII. ADDITIONAL TERMS AND CONDITIONS

- A. This permit does not relieve the Permittee of the responsibility to conduct, maintain and operate the regulated activity in compliance with all applicable requirements of any federal, municipal or other state agency. Nothing in this permit shall relieve the Permittee of other obligations under applicable federal, state and local law.

- B.** Any representative of the DEEP may enter the Permittee's site in accordance with constitutional limitations at all reasonable times without prior notice, for the purposes of inspecting, monitoring and enforcing the terms and conditions of this permit and applicable state law.
- C.** This permit may be revoked, suspended, modified or transferred in accordance with applicable law.
- D.** This permit is subject to and in no way derogates from any present or future property rights or other rights or powers of the State of Connecticut and conveys no property rights in real estate or material, nor any exclusive privileges, and is further subject to any and all public and private rights and to any federal, state or local laws or regulations pertinent to the facility or regulated activity affected thereby. This permit shall neither create nor affect any rights of persons of municipalities who are not parties to this permit.
- E.** Any document, including any notice, which is required to be submitted to the commissioner under this permit shall be signed by a duly authorized representative of the Permittee and by the person who is responsible for actually preparing such document, each of whom shall certify in writing as follows: "I have personally examined and am familiar with the information submitted in this document and all attachments thereto, and I certify that based on reasonable investigation, including my inquiry of those individuals responsible for obtaining the information, the submitted information is true, accurate and complete to the best of my knowledge and belief. I understand that any false statement made in the submitted information may be punishable as a criminal offense under Section 22a-175 of the Connecticut General Statutes, under Section 53a-157b of the Connecticut General Statutes, and in accordance with any applicable statute."
- F.** Nothing in this permit shall affect the commissioner's authority to institute any proceeding or take any other action to prevent or abate violations of law, prevent or abate pollution, recover costs and natural resource damages, and to impose penalties for violations of law, including but not limited to violations of this or any other permit issued to the Permittee by the commissioner.
- G.** Within 15 days of the date the Permittee becomes aware of a change in any information submitted to the commissioner under this permit, or that any such information was inaccurate or misleading or that any relevant information was omitted, the Permittee shall submit the correct or omitted information to the commissioner.
- H.** The date of submission to the commissioner of any document required by this permit shall be the date such document is received by the commissioner. The date of any notice by the commissioner under this permit, including but not limited to notice of approval or disapproval of any document or other action, shall be the date such notice is personally delivered or the date three days after it is mailed by the commissioner, whichever is earlier. Except as otherwise specified in this permit, the word "day" means calendar day. Any document or action which is required by this permit to be submitted or performed by a date which falls on a Saturday, Sunday or legal holiday shall be submitted or performed by the next business day thereafter.
- I.** Any document required to be submitted to the commissioner under this permit shall, unless otherwise specified in writing by the commissioner, be directed to: Office of Director; Engineering & Enforcement Division; Bureau of Air Management; Department of Energy and Environmental Protection; 79 Elm Street, 5th Floor; Hartford, Connecticut 06106-5127.